

U.S. Serial No. 10/002,576
 Reply to Office Action of: 02/28/2003
 Family Number: P2001J062

Page 2 of 4

Amendments To The Claims

(B)

GROUP 1700

MAY 28 2003

RECEIVED

RECEIVED
JUN 04 2003
TC 1700

1. (Currently Amended) A process for producing pearlite from an iron containing article comprising the steps of, (a) heating an iron containing article comprising at least 50 wt % iron for a time and at a temperature sufficient to convert at least a portion of said article from a ferritic structure to an austenitic structure, (b) exposing said austenitic structure, for a time sufficient and at a temperature of about 727 to about 900°C, to a carbon supersaturated CO/H₂ environment consisting essentially of CO and 10 to 50 vol% H₂, and having a carbon activity greater than about 1, to diffuse carbon into said austenitic structure and (c) cooling said iron containing article to form a continuous pearlite structure.
2. (Original) The process of claim 1 wherein said iron containing article further comprises silicon, manganese, and mixtures thereof.
3. (Cancelled)
4. (Cancelled)
5. (Cancelled)
6. (Original) The process of claim 1 wherein said time sufficient to diffuse carbon into the austenitic structure ranges from about 1 minute to about 50 hours.
7. (Original) The process of claim 6 wherein said thickness of pearlite is at least about 10 microns.
8. (Cancelled)
9. (Original) The process of claim 1 wherein the iron containing article, contains less than 0.77 wt% carbon.